

Tableau d'équivalence des principales dimensions roues motrices

Pneus Standard	ContiContract AC 85	ContiContract AC 70T AC 70G	ContiContract AC 65	Grand volume SVT AC 70 H	Étroit AC85C AC90
6.50 R 16		260/70 R 16			
7.50 R 16		280/70 R 16			
7.50 R 18		280/70 R 18			
9.50 R 20		275/80 R 20			
		300/70 R 20			
11.2 R 20	280/85 R 20	320/70 R 20			
12.4 R 20		360/70 R 20	420/65 R 20		
11.2 R 24	280/85 R 24	320/70 R 24			
12.4 R 24	320/85 R 24	360/70 R 24			
13.6 R 24	340/85 R 24	380/70 R 24	440/65 R 24		
14.9 R 24	380/85 R 24	420/70 R 24	480/65 R 24		270/80 R 32
16.9 R 24	420/85 R 24	480/70 R 24	540/65 R 24		270/80 R 36
11.2 R 28	280/85 R 28				
12.4 R 28	320/85 R 28				270/80 R 32
13.6 R 28	340/85 R 28	380/70 R 28	440/65 R 28		
14.9 R 28	380/85 R 28	420/70 R 28	480/65 R 28		320/85 R 32
16.9 R 28	420/85 R 28	480/70 R 28	540/65 R 28		320/90 R 32
18.4 R 28			600/65 R 28		
14.9 R 30	380/85 R 30	420/70 R 30			
16.9 R 30	420/85 R 30	480/70 R 30	540/65 R 30	500/85 R 24	
			600/65 R 28		
18.4 R 30	460/85 R 30		600/65 R 30	600/70 R 30	
			540/65 R 34		
12.4 R 32	300/85 R 32				270/80 R 36
14.9 R 34	380/85 R 34				
16.9 R 34	420/85 R 34	480/70 R 34	540/65 R 34	600/70 R 30	300/85 R 42
18.4 R 34	460/85 R 34	520/70 R 34	600/65 R 34	710/60 R 30	300/95 R 42
13.6 R 36	13.6 R 36 (*)				
13.6 R 38	340/85 R 38		540/65 R 34		
16.9 R 38	420/85 R 38	480/70 R 38	540/65 R 38		
18.4 R 38	460/85 R 38	520/70 R 38	600/65 R 38	650/75 R 32	270/95 R 48
20.8 R 38	520/85 R 38	580/70 R 38	650/65 R 38	650/65 R 38	340/85 R 48
				800/65 R 32	380/90 R 46
18.4 R 42	460/85 R 42			900/60 R 32	
20.8 R 42	520/85 R 42	710/70 R 38	650/65 R 42	710/70 R 38	460/85 R 46
				800/70 R 32	
				1050/50 R 32	
14.9 R 46	380/85 R 46	580/70 R 38	650/65 R 38		
18.4 R 46	460/85 R 46	710/70 R 38	650/65 R 42		
20.8 R 46	520/85 R 46			900/60 R 38	
				650/85 R 38	

AC65

AC90

Changement de jante nécessaire